

CubiStack

Allimentazione a Legna / Wood-Fired Heating






Wood



Long



Slim



CUBISTACK

Potenza Nominale* Heat Output - Puissance Restituée - Wärmeleistung	kW	7,5	Polveri - Dust - Poussieres - Staub (13% di O ₂)	mg / Nm ³	24
Potenza minima e massima - Minimum and maximum heat output - Puissance minimale et maximale - Minimal und Maximalleistung	kW	4 - 9	Consumo di Legna - Wood Consumption Consommation de Bois - Holzverbrauch	kg / h	2,2
Volume Riscaldabile - Heating Capacity Volume Chauffé - Beheizbare Raumgröße	m ³	100 - 260	Temperatura Fumi - Smoke Temperature Temperature des Fumées - Abgastemperatur	°C	204
Rendimento Efficiency - Rendement - Wirkungsgrad	%	81	Diametro Scarico Fumi - Flue Pipe Diameter Diamètre Conduit de Fumées - Rauchrohrdurchmesser	cm	15
Emissione Monossido di Carbonio - Carbon Monoxide Emission - Emission Monoxyde de Carbone Kohlenmonoxidemission (% CO 13% O ₂)	%	0,1	Tiraggio Draft - Dépression Conduit - Schornsteinzug	Pa	12
*Conforme, Complies UNI EN 13240 DEUTSCHLAND BimSchV 2			Peso Complessivo Total Weight - Poids Total - Gesamtgewicht	kg	300

Allimentazione a Legna • Wood-Fired Heating • Chauffage au Bois • Holzfeuerung